

AE 201 Indicator



Speed, Performance, Value - Perfect Balance

- Designed for flexibility and accuracy** Use in normal weighing mode or select the animal weighing mode to use the indicator as a person or animal scale. Display hold and automatic memory accumulation make your job easier. Kilograms / pound selectable. Displays up to 1:15,000 divisions with selectable readability from 0.001Kg to 50Kg
- Digital filters for stability** Select from a wide range of filters to accommodate for unstable environments.
- Ready for Communication** The standard RS232 port allows data output to computers or printers.
- Power Choices** Operate the AE 201 on the internal rechargeable battery for full portability or use the AC adapter (both included).
- Plus these standard features:** Simple set-up, programming, and operation plus keyboard calibration and set-up, preset or manual tare, splash-proof keypad, bright LED display, low battery indicator, and auto power-off.



The AE201 is a multi-purpose weighing indicator that can be used for a wide range of applications. With the capacity to run up to eight loadcells (maximum 350 ohm each) and a large easy-to-read LED display this indicator provides faster readings. The AE201 is today's best value in indicators with digital filters, memory accumulation, tare choices, display hold, an RS232 interface, plus an internal rechargeable battery and an AC adapter included.



Technical Specifications

General Specifications

Model	AE-201 Indicator
Units of measurement	Kilogram (kg), Pound (lb)
Interface	Rs-232 Interface
Power supply	External power supply: 230VAC / 110VAC, 50/60Hz. 10 watts. Internal battery: 6V lead acid battery, charged by internal power supply
Display	LED
Load cells	Minimum 40 ohm load cells, maximum 1200 ohm
Excitation voltage	5V, 125mA. Minimum 40 ohm load cells, maximum 1200 ohm (up to e
Housing	ABS Plastic
Sensitivity	0.7 μ v / internal increment
Connector	9 pin d sub-miniature socket
Readability	Selectable, 0.001kg to 50kg
Zero input range	0 to +2.5mv
Input range	0 to 15mv

NOVA-TECH
INTERNATIONAL
 800 Rockmead Dr Ste 102 • Houston, TX 77339-2112
 Tel: (281) 359-8538 • Toll Free Tel: (866) 433-6682
 Fax: (281) 359-0084 • Toll Free Fax: (866) 433-6684
 sales@novatech-usa.com • www.novatech-usa.com



Adam Equipment - offices worldwide