



# CFC Floor Counting Scales



## Speed, Performance, Value - Perfect Balance

- **Large stainless steel platform** The generous 20.7" x 16.7" platform is designed to withstand industrial applications.
- **Power choices** Use the AC adapter or switch to the internal rechargeable battery when portability is needed ( both included.)
- **Mountable indicator** The CFC indicator can be mounted on the enclosed pillar or used on the bench - depending on your viewing needs.
- **All the data at one glance** See weight, unit weight, and count all at the same time on the display.
- **Internal counting accuracy** With internal resolution of 1:400,000, the CFC will count small parts, reducing the need for two units and allowing greater accuracy of your parts.
- **Optional bi-directional RS232** Connect to a PC or printer to output your weighing data or send selected information to the scale using the two-way communication feature.
- **Plus these standard features:** Simple set-up and operation, splash-proof keypad, backlit LCD, auto-calibration through the keypad, overload indicator, memory accumulation, preset LCD, auto-calibration through the keypad, overload indicator, memory accumulation, preset count with alarm, low-battery indicator, and auto power-off.



CFC floor counting scales simplify complex counting applications involving heavier loads.

The CFC display shows weight, unit weight, and number of parts simultaneously for quick and convenient analysis.



### Technical Specifications

Model	CFC 130a	CFC 330a	CFC 660a
Maximum capacity	130lb / 60kg	330lb / 150kg	660lb / 300kg
Readability	0.01lb / 5g	0.02lb / 10g	0.05lb / 20g
Resolution	1:12000	1:15000	1:15000
Tare range	-130lb	-330lb	-660lb
Repeatability	0.01lb / 5g	0.02lb / 10g	0.05lb / 20g
Linearity (±)	0.02lb / 10g	0.04lb / 20g	0.1lb / 40g
Platform size	16.7×20.7" / 425×525mm		

### General Specifications

Tare functions	Full
Typical stabilisation time	2 Sec
Interface	RS-232 bi-directional Interface (Optional)
Power supply	9 VDC, 800 mA from external adapter Internal rechargeable battery (up to 70 hours operation)
Calibration	Automatic External
Display	3 x 6 digits LCD digital display
Housing	Indicator: ABS plastic, Top Pan: Stainless Steel, Base: Cast Aluminium
Net weight	33lb
Applications	General Purpose Floor Weighing and Counting Scales
Functions	Weighing, Parts Counting, Memory Accumulation, Preset count with alarm

### Key Accessories

- RS-232 Bi-directional Interface

**NOVA-TECH**  
INTERNATIONAL

800 Rockmead Dr Ste 102 • Houston, TX 77339-2112  
Tel: (281) 359-8538 • Toll Free Tel: (866) 433-6682  
Fax: (281) 359-0084 • Toll Free Fax: (866) 433-6684  
sales@novatech-usa.com • www.novatech-usa.com




135

Adam Equipment - offices worldwide