



FLEX SEAL™

Does what an insulation coating should do... and more!

Dirt and microbes continuously impact, and are absorbed by, HVAC insulation. Once contaminated, insulation is almost impossible to clean.

Old, loose fiberglass particles are known to blow off, causing environmental concerns.

If fumes and long drying time has made you hesitate to use HVAC coatings, you've been waiting for Flex Seal™.

Flex Seal's™ low odor and fast drying time gives you a real advantage in coating insulation, and the interior and exterior of HVAC systems.

APPLY IN A SNAP!

Simply apply Flex Seal with a brush, roller, or use an airless sprayer. The airless sprayer will provide the smoothest surface. You'll get from 75 to 150 square feet of coverage, depending on the porosity on the surface and the thickness of the application.

SAFE AND EASY TO USE!

Flex Seal™ is breathable. It will allow water vapor to pass through its structure, so any moisture still resident inside insulation will be allowed to evaporate out.

Flexibility and abrasion resistance allows you to use disinfectants and cleaners to wipe or scrub surfaces sealed with Flex Seal™, so you can have a well maintained unit

LOW ODOR. QUICK DRYING

Water-based Flex Seal™ is free of odor producing additives. Flex Seal™ will be dry to the touch in about 2 hours, depending on the temperature and humidity.



FLEX SEAL

FLEX SEAL™

Does what an insulation coating should do... and more!

Technical DATA

PERFORMANCE

- Low odor
- ASTM certified; zero (0) flame spread
- Won't support combustion
- Stays flexible
- Fast drying - quick turn around time
- Washable
- Chemically resistant
- Won't flake or crack
- Can be frozen - No need for special storage
- Not affected by freezing - Up to 5 freeze-thaw cycles
- Prevents fiberglass emissions

INGREDIENTS

Water-Based

PHYSICAL CHARACTERISTICS

- Viscous, white coating
- Minimal odor
- Water clean-up
- Available in 2 or 5 gallon containers
- Low HMIS hazard rating

NOVA-TECH
INTERNATIONAL
800 Rockmead Dr Ste 102 • Houston, TX 77339-2112
Tel: (281) 359-8538 • Toll Free Tel: (866) 433-6682
Fax: (281) 359-0084 • Toll Free Fax: (866) 433-6684
sales@novatech-usa.com • www.novatech-usa.com