

# OAKION®

## Waterproof Dual Parameter PCTestr™ 35 and PTTestr™ 35

### Data Sheet

- Two important measurements in one instrument
- Choose from two models –  
Conductivity and pH *or* TDS and pH
- Displays measured value along with temperature –  
simply press a key to toggle between pH and Conductivity
- Waterproof, dustproof housings float
- Push-button calibration, HOLD function, and error messages

Never watch a tester sink to the bottom of your tank or pond! These waterproof testers float, so there's no need to worry. Valox® housing and stainless steel electrodes offer good chemical compatibility and durability. All waterproof Testrs have replaceable sensors. Reuse the meter body many times without losing waterproof and dustproof protection.



WD-35425-00

WD35425-05

### Specifications & Ordering Information

Catalog number	WD-35425-00		WD-35425-05	
Description	Waterproof PCTestr 35		Waterproof PTTestr 35	
Range				
Conductivity	0 to 1999 µS	2.00 to 20.00 mS	–	–
TDS	–	–	0 to 999 ppm	1.0 to 10.00 ppt*
pH	0.0 to 14.0			
Temperature	–0.0 to 50.0°C			
Resolution				
Conductivity	1 µS	0.01 mS	–	–
TDS	–	–	1 ppm	0.01 ppt
pH	0.1 pH			
Temperature	0.1°C			
Accuracy	pH: ±0.1 pH, Conductivity: ±1% full scale, Temperature: ±0.5°C, ±0.9°F			
Temperature compensation	Automatic, 0 to 50°C; 2% per °C			
Calibration	One-point push-button calibration			
Power	Four 1.5 V alkaline batteries (included)			
Display	4-digit LCD, dual line			
Dimensions	6 1/2"L x 1 1/2"W x 1 1/2"H			

\*Maximum TDS range based on TDS factor of 0.5

### Accessories

WD-35425-50 Replacement sensor

WD-09377-16 Replacement batteries, 1.5 V. Pack of six

WD-35624-45 Beltloop Carrying Pouch

**NOVA-TECH**  
INTERNATIONAL

800 Rockmead Dr Ste 102 • Houston, TX 77339-2496  
Tel: (281) 359-8538 • Toll Free Tel: (866) 433-6682  
Fax: (281) 359-0084 • Toll Free Fax: (866) 433-6684  
sales@novatech-usa.com • www.novatech-usa.com